
FI MD GEH

High pressure filter 400bar



without bypass valve, without clogging indicator					
-10 °C					
120 °C					
Filter head of GGG					
up to 315 bar					
without filter element					





Note

Dimension "L": clearance required for changing the filter element

Description

Pressure filter for pipeline installation

Connector for clogging indicator M20 x 1.5 sealed with bolt

Ordering information

Filter element is not included. Please order separately.

Item										
Identification	for filter type	G1	L	L1	L2	ØA	ØВ	BD	AF	Weight
			(mm)	(mm)	(mm)	(mm)	(mm)	(bar)	(mm)	(kg)
FI MD GEH N 040 050 G12	FI MD 040, 050	G 1/2"	80,0	189,0	31,0	92,0	66,0	315	27	3,60
FI MD GEH N 060 075 G34	FI MD 060, 080	G 3/4"	80,0	267,0	31,0	92,0	66,0	315	27	3,90
FI MD GEH N 080 090 G34	FI MD 080, 090	G 3/4"	80,0	343,0	31,0	92,0	66,0	315	27	5,10
FI MD GEH N 170 190 G114	FI MD 170, 190	G 1.1/4"	110,0	257,0	32,0	142,0	109,0	210	27	8,50
FI MD GEH N 240 260 G114	FI MD 240, 260	G 1.1/4"	110,0	371,0	32,0	142,0	109,0	210	30	15,30

BD = Working pressure

Accessories	
HK VA PIS M	Clogging indicator mechanical
HK VA PIS EL	Clogging indicator electrical

Spare part for following products

FI MD 315 Medium pressure filter 315 bar

Additional elements

FI HD E MA Filter element for high-pressure filter MA