SKF IR HA

Screwed coupling fixed half

Properties

Application	Hydraulic hammers, rams etc.
Connection 1	BSP cylindrical internal threads
Sealing form 1	for screw-in pins with shapes A, B and if necessary E
Temp. range	-25° C to +100° C
Material	Steel
Surface	electro galvanised



Description

This coupling has been specially designed for use in the toughest conditions and can withstand severe vibrations and compression.
The inner parts can be replaced when worn (repair possible).

Item

Identification	DN*	Connecting thread	AF (mm)	Coupling thread	Operating pressure (bar)
SKF 10 IR HA	10	G 3/8" -19	22	Rd. 36x3	600,0
SKF 13 IR HA	12	G 1/2" -14	26	Rd. 40x3	450,0
SKF 20 IR HA	19	G 3/4" -14	30	Rd. 45x3	400,0
SKF 25 IR HA	25	G 1" -11	40	Rd. 58x4	350,0
SKF 32 IR HA	31	G 1.1/4" -11	48	Rd. 65x5	320,0
SKF 40 IR HA	38	G 1.1/2" -11	55	Rd. 75x5	300,0

DN = Nominal diameter, nominal width – SF gek. = Safety factor coupled – AF = Width across flats

Accessories

SK ZUB SLF HA	Sealing spring for HA coupling
SK ZUB AH HA	Welded-on clip for HA coupling
SK ZUB DK HA	Conical nipple for HA coupling
SK ZUB GR HA	Threaded ring for HA coupling
SKF ZUBS HA	Dust protector for SKF..HA
SKF ZUBS SR HA	Circlip for HA coupling

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.