

LKM HR ST DK

Plug-in coupling sleeve (air) with locking mechanism

HANSA FLEX

Properties

Design	Quick release coupling sleeve
Connection 1	BSP external thread, cylindrical
Connection 2	
Operating pressure	max. 12 bar
Flow rate air	1.800 l/min (at 6 bar and $\Delta p = 1$ bar)
Media temperature	-20 °C to +70 °C
Housing	Aluminium, anodised
Thread	Nickel-plated brass
Internal parts	Stainless steel
Button, valve	Hardened, galvanised steel
Sealant	NBR



Note

Not suitable for hitting / pulsating tools.
Further information on request

Description

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414.

Item				
Identification	Connecting thread	Connection	Length (mm)	AF (mm)
LKM 06 HR ST DK	G 1/4" -19	G 1/4 male	70,5	21
LKM 10 HR ST DK	G 3/8" -19	G 3/8 male	70,0	21
LKM 13 HR ST DK	G 1/2" -14	G 1/2 male	72,5	25