

# TUEG LMA VA

Dairy coupling conical coupling, with smooth tail, stainless steel

**HANSA FLEX**

## Properties

<b>Application</b>	Food industry
<b>Connection 1</b>	Conical coupling, form SD with NUT- union nut form F
<b>Sealing form 1</b>	Outer cone
<b>Standard</b>	DIN 11851 DIN 405-1
<b>Construction</b>	straight
<b>Material</b>	Stainless steel 1.4301



## Item

Identification	DN	PN (bar)	G1
TUEG 25 LMA VA	25	40	Rd 52 x 1/6"
TUEG 32 LMA VA	32	40	Rd 58 x 1/6"
TUEG 38 LMA VA	38	40	Rd 65 x 1/6"
TUEG 50 LMA VA	50	25	Rd 78 x 1/6"
TUEG 63 LMA VA	63	25	Rd 95 x 1/6"
TUEG 75 LMA VA	76	25	Rd 110 x 1/4"
TUEG 100 LMA VA	100	25	Rd 130 x 1/4"

## Accessories

<b>KS AL</b>	Clamp ring fitting, aluminium
<b>KS FIX AL</b>	Clamping shell for pinning, aluminium
<b>NMHAS GVA</b>	Slotted nut hook wrench with hinge, stainless steel