


# SILIKON BL

Silicone hose, blue

## Properties

<b>Application</b>	Cooler hose
<b>Special features</b>	very highly resistant to high and low temperatures very good resistance to coolants, oils and cleaning agents very good resistance to ozone, UV and classic aging processes the suppleness of the silicone enables easy installation
<b>Standard</b>	SAE J20R1 CLASS A
<b>Inner layer</b>	Silicone blue
<b>Insert</b>	Textile insert
<b>Outer layer</b>	Silicone blue
<b>Colour</b>	blue
<b>Temp. min.</b>	-60 °C
<b>Temp. max.</b>	200 °C
<b>Media</b>	Cooling fluids hot air



## Item

Identification	Internal Ø (mm)	External Ø (mm)	Operating pressure (bar)	Wall thickness (mm)	Burst pressure (bar)
SILIKON 08-4 BL	8	16	20,0	4,0	60
SILIKON 10-4 BL	10	18	20,0	4,0	60
SILIKON 12-4 BL	12	20	19,0	4,0	57
SILIKON 14-4 BL	14	22	18,0	4,0	54
SILIKON 16-4 BL	16	24	15,0	4,0	45
SILIKON 18-4 BL	18	26	13,0	4,0	39
SILIKON 20-4 BL	20	28	12,0	4,0	36
SILIKON 22-4 BL	22	30	12,0	4,0	36
SILIKON 25-4.5 BL	25	34	11,0	4,5	33
SILIKON 28-4.5 BL	28	37	10,0	4,5	30
SILIKON 30-4.5 BL	30	39	10,0	4,5	30
SILIKON 32-4.5 BL	32	41	9,0	4,5	27
SILIKON 35-4.5 BL	35	44	8,0	4,5	24
SILIKON 38-4.5 BL	38	47	7,0	4,5	21
SILIKON 40-4.5 BL	40	49	7,0	4,5	21
SILIKON 45-4.5 BL	45	54	6,0	4,5	18
SILIKON 48-4.5 BL	48	57	6,0	4,5	18
SILIKON 50-4.5 BL	50	59	6,0	4,5	18
SILIKON 57-4.5 BL	57	66	5,0	4,5	15
SILIKON 60-4.5 BL	60	69	5,0	4,5	15
SILIKON 65-5.5 BL	65	76	5,0	5,5	15
SILIKON 70-5.5 BL	70	81	4,0	5,5	12
SILIKON 80-6 BL	80	92	3,0	6,0	9

the above values relate to an ambient temperature (20 °C); we recommend a 20 % operating pressure reduction for every 100 °C