


| Properties | | | | |
|--------------------|---------------------------------|--|--|--|
| Design | internal pressure control valve | | | |
| Operating pressure | max. 700 bar | | | |
| Connections | 3/8" Female NPT | | | |
| Material | Aluminium housing | | | |
| Scope of supply | Including manometer | | | |





Note

Attention: Please observe separate safety precautions for working with 700 bar equipment (see technical information)!

Description

The use of 2-stage pumps is recommended for cylinders with large oil volumes.

Hand lever can be used as carrying handle after locking.

| Item | | | | | | | | | | | |
|----------------|------------------------|--------|---------------------|---------------------|-----------------------|-----------------------|------|------|------|------|--------|
| Identification | useful oil vol- ume | Levels | Volume level 1 max. | Volume level 2 max. | Pressure level 1 max. | Pressure level 2 max. | Α | В | С | D | Weight |
| | (cc) | | (cc) | (cc) | (bar) | (bar) | (mm) | (mm) | (mm) | (mm) | (kg) |
| HK WW WH1 | 500,0 | 2 | 7,2 | 0,9 | 20 | 700 | 290 | 60 | 174 | 394 | 4,3 |
| HK WW WH2 | 900,0 | 2 | 17,0 | 1,7 | 20 | 700 | 460 | 60 | 174 | 565 | 5,3 |

| Accessories | |
|-------------|-------------------------------------|
| NY 2100 | Thermoplastic extreme pressure hose |
| GKS | Rubber antikink protection |
| PNY 2100 HN | Swage nipple, AGN |
| PHY 2100 | Swage ferrule, NY 2100 |
| SKL HN SP | Screwed coupling, loose half |
| SKL ZUBS SP | Dust protection for SKLSP |
| SKF IN SP | Screwed coupling fixed half |
| SKF ZUBS SP | Dust protection for SKFSP |