

STOP LOCK

Hose retention system

Properties

| | |
|--------------------|--|
| Material | Steel |
| Application | Personal protection against whipping hose |
| Temp. range | -30 °C to +150 °C |
| Approval | BGR 237 DIN EN ISO 4413 BGI 5100 Machinery Directive 2006/42/EC |



Item

| Identification | for machine fixation point Ø | for hose DN | for external hose Ø | Max. working pressure (bar) |
|---------------------------|------------------------------|-------------|---------------------|-----------------------------|
| STOP LOCK 45 85 | 11.5-15.5mm | 02 - 04 | 4.5-8.5mm | 630 |
| STOP LOCK 1119 | 12-20mm | 05 - 08 | 11-19mm | 450 |
| STOP LOCK 1119 UHP | 12-20mm | 06 | 11-19mm | 700 |
| STOP LOCK 1728 | 18-24mm | 10 - 12 | 17-28mm | 450 |
| STOP LOCK 2331 | 22-30mm | 16 | 23-31mm | 420 |
| STOP LOCK 2635 | 28-36mm | 19 | 26-35mm | 420 |
| STOP LOCK 3444 | 32-42mm | 25 | 34-44mm | 420 |
| STOP LOCK 4352 | 38-52mm | 31 | 43-52mm | 210 |
| STOP LOCK 5061 | 44-52mm | 38 | 50-61mm | 200 |
| STOP LOCK 6074 | 56-62mm | 51 | 60-74mm | 185 |
| STOP LOCK 4352 HP | 38-52mm | 31 | 43-52mm | 350 |
| STOP LOCK 5061 HP | 44-52mm | 38 | 50-61mm | 310 |
| STOP LOCK 6074 HP | 56-62mm | 51 | 60-74mm | 270 |
| STOP LOCK 4352 UHP | 38-52mm | 31 | 43-52mm | 500 |
| STOP LOCK 5061 UHP | 44-52mm | 38 | 50-61mm | 450 |
| STOP LOCK 6074 UHP | 56-62mm | 51 | 60-74mm | 420 |

Accessories

| | |
|-----------------------|-------------------------------|
| STOP LOCK-KIT | Hose retention system toolkit |
| STOP LOCK-TAPE | Hose retention system tape |