

### Properties

Material	Steel
Application	Personal protection against whipping hose
Temp. range	-30 °C to +150 °C
Approval	BGR 237 DIN EN ISO 4413 BGI 5100 Machinery Directive 2006/42/EC



### Item

Identification	for machine fixation point Ø	for hose DN	for external hose Ø	Max. working pressure (bar)
<b>STOP LOCK 45 85</b>	11.5-15.5mm	02 - 04	4.5-8.5mm	630
<b>STOP LOCK 1119</b>	12-20mm	05 - 08	11-19mm	450
<b>STOP LOCK 1119 UHP</b>	12-20mm	06	11-19mm	700
<b>STOP LOCK 1728</b>	18-24mm	10 - 12	17-28mm	450
<b>STOP LOCK 2331</b>	22-30mm	16	23-31mm	420
<b>STOP LOCK 2635</b>	28-36mm	19	26-35mm	420
<b>STOP LOCK 3444</b>	32-42mm	25	34-44mm	420
<b>STOP LOCK 4352</b>	38-52mm	31	43-52mm	210
<b>STOP LOCK 5061</b>	44-52mm	38	50-61mm	200
<b>STOP LOCK 6074</b>	56-62mm	51	60-74mm	185
<b>STOP LOCK 4352 HP</b>	38-52mm	31	43-52mm	350
<b>STOP LOCK 5061 HP</b>	44-52mm	38	50-61mm	310
<b>STOP LOCK 6074 HP</b>	56-62mm	51	60-74mm	270
<b>STOP LOCK 4352 UHP</b>	38-52mm	31	43-52mm	500
<b>STOP LOCK 5061 UHP</b>	44-52mm	38	50-61mm	450
<b>STOP LOCK 6074 UHP</b>	56-62mm	51	60-74mm	420

### Accessories

<b>STOP LOCK-KIT</b>	Hose retention system toolkit
<b>STOP LOCK-TAPE</b>	Hose retention system tape