

HK DLEH
Poppet valve NG 6

Properties

Scope of supply	with coil, 24 DC without plug
Operating pressure	P, A, B: max. 350bar / T: max. 210bar
Volumetric flow	max. 30 l/min (note characteristic curves)
Connection	ISO/Cetop 03 size 6
Mounting	4 pcs. socket head screw M5x50 12.9





Description

2-way or 3-way seat valves with 2 switching positions
Solenoids and all moving parts switch internally in oil
Solenoid coil 24 VDC with emergency hand operation

Item

Identification	Type	Volumetric flow max. (L/min)	Design	Weight (kg)
HK DLEH 2A X 24DC	2/2	12,0	power-off open	1,5
HK DLEH 2C X 24DC	2/2	12,0	power-off closed	1,5
HK DLEH 3A X 24DC	3/2	12,0	power-off open	1,5
HK DLEH 3C X 24DC	3/2	12,0	power-off closed	1,5
HK DLEHM 3A X 24DC	3/2	30,0	power-off open	1,7
HK DLEHM 3C X 24DC	3/2	30,0	power-off closed	1,7

Accessories

HK SP DIN 43650	Electrical plug for solenoid coil DIN 43650 / ISO 4400
HK M HK DH	Screw set for NG 6 valves type HK DH / DG4V3

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.