

## Properties

<b>Design</b>	with central phase compensation valve external leak oil discharge Adjustment range DBV: 70-210 bar
<b>Rotational speed range</b>	1200 - 2700 U/min
<b>Pressure difference</b>	max. 30 bar (between the sections)
<b>Recommended speed</b>	1800 - 2000 rpm

## Note

Before commissioning the system, the first running-in of the gear flow divider should be under no load.

## Description

This flow divider is used to supply four independent hydraulic circuits with just one pump

Division error approx. 3%

Equal pressure setting for all sections

Valves settable from 70-210 bar, other setting ranges on request

Modification to internal leak oil discharge possible - For this, remove the cylinder head screw in port T and close off the port with G1/2" blind plug (modification recommended only after consultation!)

Configuration of gear flow dividers:  $q_i = Q/z * 1000/n$

$q_i$  = displacement/section [cm<sup>3</sup>];  $Q$  = total intake volumetric flow [l/min];  $z$  = no. of sections;  $n$  = rotating speed [rpm]

## Item

Identification	Intake volume per section (cc)	p1 max. (bar)	Flow per element min. (L/min)	Flow per element max. (L/min)	Flow per element (L/min)	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	F (mm)	F1 (mm)	H (mm)	Li (mm)	Ø R1 (mm)	Weight (kg)
HK 9RS 04E 01	0,17	210	0,20	1,20	0,40	29,3	292,2	46	32,5	54,25	88,3	122,3	50	278	6,5	2,1
HK 9RS 04E 02	0,25	210	0,30	1,80	0,70	29,9	294,6	46	32,5	54,25	88,3	122,3	50	281	6,5	2,1
HK 9RS 04E 04	0,45	210	0,60	3,00	1,20	31,5	301,0	46	32,5	54,25	88,3	122,3	50	287	6,5	2,1
HK 9RS 04E 05	0,57	210	0,80	3,80	1,50	32,5	305,0	46	32,5	54,25	88,3	122,3	50	291	6,5	2,2
HK 9RS 04E 06	0,76	210	1,00	4,80	2,00	34,0	311,0	46	32,5	54,25	88,3	122,3	50	297	6,5	2,2

p1 = max. working pressure