

## Características

|                             |                               |
|-----------------------------|-------------------------------|
| Conexión 1                  | Rosca interior UN/UNF         |
| Construcción                | Contratuercas                 |
| Norma                       | ISO 8434-2                    |
| Material                    | Acero                         |
| Protección de la superficie | con revestimiento galvanizado |



## Artículo

| Denominación | G1             | L1<br>(mm) | SW<br>(mm) |
|--------------|----------------|------------|------------|
| KM 04 UNF    | 7/16" -20 UNF  | 6,4        | 17         |
| KM 05 UNF    | 1/2" -20 UNF   | 6,4        | 19         |
| KM 06 UNF    | 9/16" -18 UNF  | 6,9        | 22         |
| KM 08 UNF    | 3/4" -16 UNF   | 7,9        | 24         |
| KM 10 UNF    | 7/8" -14 UNF   | 9,1        | 30         |
| KM 12 UNF    | 1.1/16" -12 UN | 10,4       | 36         |
| KM 16 UNF    | 1.5/16" -12 UN | 10,4       | 41         |
| KM 20 UNF    | 1.5/8" -12 UN  | 10,4       | 50         |
| KM 24 UNF    | 1.7/8" -12 UN  | 10,4       | 55         |
| KM 32 UNF    | 2.1/2" -12 UN  | 10,4       | 70         |

SW = ancho de llave