

PHF 100

Engaste a presión, TF 100

HANSA FLEX

Características

| | |
|-----------------------------|-------------------------------|
| Clase de engaste | Engaste sin pelar |
| Material | Acero |
| Protección de la superficie | con revestimiento galvanizado |



Artículo

| Denominación | DN* | Tamaño | Pulgadas | D1 (mm) | D3 (mm) | LF (mm) |
|--------------|-----|--------|----------|------------|------------|------------|
| PHF 104 | 5 | 3 | 3/16" | 13 | 8,3 | 30 |
| PHF 106 | 6 | 4 | 1/4" | 15 | 10,6 | 32 |
| PHF 108 | 8 | 5 | 5/16" | 17 | 12,2 | 33 |
| PHF 110 | 10 | 6 | 3/8" | 19 | 13,7 | 33 |
| PHF 113 | 12 | 8 | 1/2" | 24 | 18,0 | 37 |
| PHF 116 | 16 | 10 | 5/8" | 27 | 21,5 | 37 |
| PHF 120 | 19 | 12 | 3/4" | 32 | 25,0 | 41 |
| PHF 125 | 25 | 16 | 1" | 38 | 31,0 | 41 |

DN = diámetro nominal, ancho nominal

Variantes de producto

PHF 100 VA Engaste a presión, TF 100, Acero fino