

### Características

**Conexión 1** Roscas exteriores BSP cilíndricas

**Conexión 2** Conexión de tubo flexible

**Material** Latón



### Artículo

| Denominación | Roscas interiores | para diámetro interno tubo flexible<br>(mm) | SW<br>(mm) | Presión de servicio en bar |
|--------------|-------------------|---|------------|----------------------------|
| T 184 M      | G 1/8" -28        | 4   | 14         | PN 16                      |
| T 186 M      | G 1/8" -28        | 6   | 14         | PN 16                      |
| T 189 M      | G 1/8" -28        | 9   | 14         | PN 16                      |
| T 144 M      | G 1/4" -19        | 4   | 17         | PN 16                      |
| T 146 M      | G 1/4" -19        | 6   | 17         | PN 16                      |
| T 149 M      | G 1/4" -19        | 9   | 17         | PN 16                      |
| T 1413 M     | G 1/4" -19        | 13  | 17         | PN 16                      |
| T 386 M      | G 3/8" -19        | 6   | 19         | PN 16                      |
| T 389 M      | G 3/8" -19        | 9   | 19         | PN 16                      |
| T 3813 M     | G 3/8" -19        | 13  | 19         | PN 16                      |
| T 126 M      | G 1/2" -14        | 6   | 24         | PN 16                      |
| T 129 M      | G 1/2" -14        | 9   | 24         | PN 16                      |
| T 1213 M     | G 1/2" -14        | 13  | 24         | PN 16                      |
| T 1219 M     | G 1/2" -14        | 19  | 24         | PN 16                      |
| T 349 M      | G 3/4" -14        | 9   | 27         | PN 16                      |
| T 3413 M     | G 3/4" -14        | 13  | 32         | PN 16                      |
| T 3419 M     | G 3/4" -14        | 19  | 32         | PN 16                      |
| T 1019 M     | G 1" -11          | 19  | 26         | PN 16                      |
| T 1025 M     | G 1" -11          | 25  | 38         | PN 16                      |

SW = ancho de llave