

Características	
Campo de aplicación	Fijaciones para tubos flexibles en el ámbito de baja presión
Material	Acero
Protección de la superficie	con revestimiento galvanizado



Denominación	Rango de tensión (mm)	Ancho de cinta
		(mm)
2 OK 5-7	5 - 7	6,0
2 OK 7-9	7 - 9	6,0
2 OK 9-11	9 - 11	6,5
2 OK 11-13	11 - 13	6,5
2 OK 13-15	13 - 15	7,0
2 OK 14-17	14 - 17	7,0
2 OK 15-18	15 - 18	7,5
2 OK 17-20	17 - 20	7,5
2 OK 18-21	18 - 21	8,0
2 OK 20-23	20 - 23	8,0
2 OK 22-25	22 - 25	8,5
2 OK 23-27	23 - 27	8,5
2 OK 25-28	25 - 28	9,0
2 OK 28-31	28 - 31	9,0
2 OK 31-34	31 - 34	9,5
2 OK 34-37	34 - 37	9,5
2 OK 37-40	37 - 40	10,0
2 OK 40-43	40 - 43	10,0
2 OK 43-46	43 - 46	10,0

Variantes de producto		
2 OK VC	Pinzas de 2 estribos, galvanizado brillante de cromo	
2 OK VA	Pinzas de 2 estribos, Acero fino	