

SRS 1-6 SPW V4

Placas angulares de soldadura y atornilladas

HANSA FLEX

Características

| | |
|--------------------|-----------------------------|
| Forma constructiva | Ángulo de 90° |
| Construcción | para abrazaderas de un tubo |
| Serie | ligero |
| Norma | DIN 3015-1 |
| Material | Acero fino 1.4571 |



Artículo

| Denominación | Tamaño de las abrazaderas | B (mm) | c (mm) | e1 (mm) | e2 (mm) | G | H (mm) | L (mm) | S (mm) |
|----------------|---------------------------|-----------|-----------|------------|------------|-----|-----------|-----------|-----------|
| SRS SPW 1 A V4 | 1 | 30 | 6,6 | 20,0 | 20 | M 6 | 30 | 36,0 | 3 |
| SRS SPW 2 V4 | 2 | 30 | 6,6 | 26,0 | 26 | M 6 | 30 | 42,0 | 3 |
| SRS SPW 3 V4 | 3 | 30 | 6,6 | 33,0 | 33 | M 6 | 30 | 50,0 | 3 |
| SRS SPW 4 V4 | 4 | 30 | 6,6 | 40,0 | 40 | M 6 | 30 | 59,0 | 3 |
| SRS SPW 5 V4 | 5 | 30 | 6,6 | 52,0 | 52 | M 6 | 30 | 72,0 | 3 |
| SRS SPW 6 V4 | 6 | 30 | 6,6 | 66,0 | 66 | M 6 | 30 | 88,0 | 3 |

Variantes de producto

SRS 1-6 SPW Placas angulares de soldadura y atornilladas, Acero