
HK GEH 20 GGG

Carcasa de válvula para válvula de rosca SAE 2 vías GGG40



Características	
Material	GGG 40
Presión de servicio	máx. 350 bares
Protección de la superficie	galvanizado





Artículo													
Denominación	Perforación de válvula	A	Conexión 1,3	С	D	E	F	G	Н	Т	L	M	Peso
				(mm)	(kg)								
HK GEH 38 C0820 GGG	C0820	UNF 3/4" -16	G 3/8"	50	50	29	20	13,5	12	6	9,0	35	0,4
HK GEH 38 C1020 GGG	C1020	UNF 7/8" -14	G 3/8"	60	60	40	24	19,0	15	7	7,5	45	0,8
HK GEH 34 C1020 GGG	C1020	UNF 7/8" -14	G 3/4"	60	60	44	24	21,5	15	7	7,5	45	1,7
HK GEH 12 C1220 GGG	C1220	UNF 1.1/16" -12	G 1/2"	80	80	50	34	26,0	18	9	10,0	60	0,9
HK GEH 34 C1220 GGG	C1220	UNF 1.1/16" -12	G 3/4"	80	80	50	34	26,0	18	9	10,0	60	1,7

es accesorio para los siguientes productos				
HK EMDV	Válvula magnética de vías 2/2 EMDV			
HK RVPS	Válvula de limitación de presión RVPS			
HK PCFC	Válvula de regulación de corriente de 2 vías PCFC			