

K-PUR-BREMSSPIRALE

PUR brake coil with connection

HANSA FLEX

Características

Conexión 1 + 2	Rosca exterior métrica, cilíndrica
Norma	tested in accordance with DIN 74323 DIN 74324 ISO 7268-2 ISO 7375-2 DIN 73378 DIN 74310-2
Homologación	German Technical Surveyance Association (TÜV)- type approved (Certificate R 9910199)
Temperatura min.	-40 °C
Temperatura max.	90 °C
Material	PUR



Información adicional

- will not break at fittings
- excellent antikink characteristics – kinking leaves no defects
- longer operation length
- highly resistant to tearing off at fittings
- excellent springback characteristics
- unplasticized so no embrittlement
- resistant to oil and grease
- resistant to UV and ozon
- service life many times longer than conventional coil tubing

Artículo

Denominación	G1 + G2	Ø interior (mm)	Ø exterior (mm)	Espesor de la pared (mm)	Longitud (m)	Color
K- 07 10 13 21	M 16 x 1,5	8,0	12,0	2,0	4,50	negro
K- 07 10 13 22	M 16 x 1,5	8,0	12,0	2,0	4,50	amarillo
K- 07 10 13 23	M 16 x 1,5	8,0	12,0	2,0	4,50	rojo
K- 07 10 13 24	M 16 x 1,5	8,0	12,0	2,0	5,50	negro
K- 07 10 13 25	M 16 x 1,5	8,0	12,0	2,0	5,50	amarillo
K- 07 10 13 26	M 16 x 1,5	8,0	12,0	2,0	5,50	rojo