

# K-PUR-BREMSSPIRALE

PUR brake coil with connection

**HANSA FLEX**

## Características

<b>Conexión 1 + 2</b>	Rosca exterior métrica, cilíndrica
<b>Norma</b>	tested in accordance with DIN 74323 DIN 74324 ISO 7268-2 ISO 7375-2 DIN 73378 DIN 74310-2
<b>Homologación</b>	German Technical Surveyance Association (TÜV)- type approved (Certificate R 9910199)
<b>Temperatura min.</b>	-40 °C
<b>Temperatura max.</b>	90 °C
<b>Material</b>	PUR



## Información adicional

- will not break at fittings
- excellent antikink characteristics – kinking leaves no defects
- longer operation length
- highly resistant to tearing off at fittings
- excellent springback characteristics
- unplasticized so no embrittlement
- resistant to oil and grease
- resistant to UV and ozon
- service life many times longer than conventional coil tubing

## Artículo

Denominación	G1 + G2	Ø interior (mm)	Ø exterior (mm)	Espesor de la pared (mm)	Longitud (m)	Color
K- 07 10 13 21	M 16 x 1,5	8,0	12,0	2,0	4,50	negro
K- 07 10 13 22	M 16 x 1,5	8,0	12,0	2,0	4,50	amarillo
K- 07 10 13 23	M 16 x 1,5	8,0	12,0	2,0	4,50	rojo
K- 07 10 13 24	M 16 x 1,5	8,0	12,0	2,0	5,50	negro
K- 07 10 13 25	M 16 x 1,5	8,0	12,0	2,0	5,50	amarillo
K- 07 10 13 26	M 16 x 1,5	8,0	12,0	2,0	5,50	rojo