

K-BIMETALLTHERMOMETER 52-2

Bimetallic thermometers

HANSA FLEX

Características

| | |
|---------------------|---|
| Tipo | 52 |
| Correcc. indicación | Trimming pointer |
| Presión de servicio | Max. 25 bar (on thermowell) |
| Seleccione para eso | Thermowell (removable) with locking screw |
| Vástago sumerg. | Ø 8 mm, CrNi steel |
| Carcasa, anillo | CrNi steel |
| Ventana de insp. | Flat instrument glass |



Nota

Otras especificaciones a petición.

Descripción

Applications: Extremely versatile design for use in machine, vessel, pipeline and plant construction as well as for heating systems.

Artículo

| Denominación | Rangos de indicación | Ø (mm) | Long. vástago | Conexión |
|----------------|----------------------|--------|-----------------------------------|--|
| K- 07 20 07 26 | -30 °C to +50 °C | 63,0 | thermowell L1 = 63mm, L2 = 43mm | Flush, with collar for thermowell, Ø 18 mm |
| K- 07 20 07 27 | 0 °C to +120 °C | 63,0 | thermowell L1 = 63mm, L2 = 43mm | Flush, with collar for thermowell, Ø 18 mm |
| K- 07 20 07 28 | 0 °C to +160 °C | 63,0 | thermowell L1 = 63mm, L2 = 43mm | Flush, with collar for thermowell, Ø 18 mm |
| K- 07 20 07 29 | 0 °C to +200 °C | 63,0 | thermowell L1 = 63mm, L2 = 43mm | Flush, with collar for thermowell, Ø 18 mm |
| K- 07 20 07 30 | 0 °C to +250 °C | 63,0 | thermowell L1 = 63mm, L2 = 43mm | Flush, with collar for thermowell, Ø 18 mm |
| K- 07 20 07 31 | -30 °C to +50 °C | 63,0 | thermowell L1 = 100mm, L2 = 80mm | Flush, with collar for thermowell, Ø 18 mm |
| K- 07 20 07 32 | 0 °C to +120 °C | 63,0 | thermowell L1 = 100mm, L2 = 80mm | Flush, with collar for thermowell, Ø 18 mm |
| K- 07 20 07 33 | 0 °C to +160 °C | 63,0 | thermowell L1 = 100mm, L2 = 80mm | Flush, with collar for thermowell, Ø 18 mm |
| K- 07 20 07 34 | 0 °C to +200 °C | 63,0 | thermowell L1 = 100mm, L2 = 80mm | Flush, with collar for thermowell, Ø 18 mm |
| K- 07 20 07 35 | 0 °C to +250 °C | 63,0 | thermowell L1 = 100mm, L2 = 80mm | Flush, with collar for thermowell, Ø 18 mm |
| K- 07 20 07 36 | -30 °C to +50 °C | 63,0 | thermowell L1 = 160mm, L2 = 140mm | Flush, with collar for thermowell, Ø 18 mm |
| K- 07 20 07 37 | 0 °C to +120 °C | 63,0 | thermowell L1 = 160mm, L2 = 140mm | Flush, with collar for thermowell, Ø 18 mm |
| K- 07 20 07 38 | 0 °C to +160 °C | 63,0 | thermowell L1 = 160mm, L2 = 140mm | Flush, with collar for thermowell, Ø 18 mm |
| K- 07 20 02 11 | -30 °C to +50 °C | 100,0 | thermowell L1 = 63mm, L2 = 43mm | Flush, with collar for thermowell, Ø 18 mm |
| K- 07 20 02 12 | 0 °C to +120 °C | 100,0 | thermowell L1 = 63mm, L2 = 43mm | Flush, with collar for thermowell, Ø 18 mm |
| K- 07 20 02 13 | 0 °C to +160 °C | 100,0 | thermowell L1 = 63mm, L2 = 43mm | Flush, with collar for thermowell, Ø 18 mm |
| K- 07 20 02 14 | 0 °C to +250 °C | 100,0 | thermowell L1 = 63mm, L2 = 43mm | Flush, with collar for thermowell, Ø 18 mm |
| K- 07 20 02 15 | -30 °C to +50 °C | 100,0 | thermowell L1 = 100mm, L2 = 80mm | Flush, with collar for thermowell, Ø 18 mm |
| K- 07 20 02 16 | 0 °C to +120 °C | 100,0 | thermowell L1 = 100mm, L2 = 80mm | Flush, with collar for thermowell, Ø 18 mm |
| K- 07 20 02 17 | 0 °C to +160 °C | 100,0 | thermowell L1 = 100mm, L2 = 80mm | Flush, with collar for thermowell, Ø 18 mm |
| K- 07 20 02 18 | 0 °C to +200 °C | 100,0 | thermowell L1 = 100mm, L2 = 80mm | Flush, with collar for thermowell, Ø 18 mm |
| K- 07 20 02 19 | 0 °C to +250 °C | 100,0 | thermowell L1 = 100mm, L2 = 80mm | Flush, with collar for thermowell, Ø 18 mm |
| K- 07 20 02 20 | -30 °C to +50 °C | 100,0 | thermowell L1 = 160mm, L2 = 140mm | Flush, with collar for thermowell, Ø 18 mm |
| K- 07 20 02 21 | 0 °C to +120 °C | 100,0 | thermowell L1 = 160mm, L2 = 140mm | Flush, with collar for thermowell, Ø 18 mm |
| K- 07 20 02 22 | 0 °C to +160 °C | 100,0 | thermowell L1 = 160mm, L2 = 140mm | Flush, with collar for thermowell, Ø 18 mm |
| K- 07 20 02 23 | 0 °C to +200 °C | 100,0 | thermowell L1 = 160mm, L2 = 140mm | Flush, with collar for thermowell, Ø 18 mm |
| K- 07 20 02 24 | 0 °C to +250 °C | 100,0 | thermowell L1 = 160mm, L2 = 140mm | Flush, with collar for thermowell, Ø 18 mm |

Accesorios

| | |
|---------------------------|----------------------|
| K-SCHUTZROHRE EINSCHRAUB | Screw-in thermowells |
| K-SCHUTZROHRE EINSCHWEISS | Weld-in thermowells |