

# K-MANO ABSPV ZAPF SPAN MUF PRUEFFL

Pressure gauge valves, male - female/female, with test flange 60 x 25 x 10

**HANSA FLEX**

## Características

|                                 |  |
|---------------------------------|--|
| Presión de servicio             | max. 250 bar brass, max. 400 bar steel/<br>stainless steel         |
| Temperatura                     | Max. +120 °C with brass/steel; Max. +200 °C<br>for stainless steel |
| Material de todos los comp.     | Stainless steel  |
| Material obturador              | PTFE   |
| Carcasa                         | Brass, black-finished steel or stainless steel<br>1.4571           |
| Rueda manual                    | Plastic  |
| Tuerca racor mang. sujeción     | Steel  |
| Husillo de válv., cono de válv. | Stainless steel  |



## Nota

Otras especificaciones a petición.

## Descripción

They are used as shut-off or reducing elements for pressure gauges when measuring liquids, gases or steam.

## Artículo

| Denominación   | Rosca | PN (bar) | SW<br>(mm) | Material        |
|----------------|-------|----------|------------|-----------------|
| K- 07 20 11 34 | G 1/2 | 250      | 27         | Latón           |
| K- 07 20 11 33 | G 1/2 | 400      | 27         | Stainless steel |