

K-RMM U KUNSTSTOFF

Standard pressure gauges (pastic housing / connection radial on bottom)

HANSA FLEX

Características

| | |
|--|--|
| Tipo | 111.10 |
| Versión | Bourdon-tube pressure gauge in standard design |
| Aplicación | gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise |
| Categoría de calidad | 1.6 (Art. No. K-07200454: 2.5) |
| Temper. de medios | máx. +60 °C |
| Temp. entorno | -20 °C hasta +60 °C |
| Carcasa | Plastic |
| Órgano medidor material y mec. Indicador | Aleación de cobre |
| Ventana de insp. | Transparent plastic |



Nota

Otras especificaciones a petición.

Artículo

| Denominación | Rango de medición | Ø (mm) | Conexión |
|----------------|-------------------|--------|----------|
| K- 07 20 04 47 | -1 / 0.0 bar | 40,0 | G 1/8 |
| K- 07 20 04 48 | 0 - 1.6 bar | 40,0 | G 1/8 |
| K- 07 20 04 49 | 0 - 2.5 bar | 40,0 | G 1/8 |
| K- 07 20 04 50 | 0 - 4.0 bar | 40,0 | G 1/8 |
| K- 07 20 04 51 | 0 - 6.0 bar | 40,0 | G 1/8 |
| K- 07 20 04 52 | 0 - 10.0 bar | 40,0 | G 1/8 |
| K- 07 20 04 53 | 0 - 16.0 bar | 40,0 | G 1/8 |
| K- 07 20 04 54 | 0 - 25.0 bar | 40,0 | G 1/8 |
| K- 07 20 04 55 | 0 - 40.0 bar | 40,0 | G 1/8 |
| K- 07 20 05 51 | -1 / 0.0 bar | 50,0 | G 1/4 |
| K- 07 20 05 52 | 0 - 1.0 bar | 50,0 | G 1/4 |
| K- 07 20 05 53 | 0 - 1.6 bar | 50,0 | G 1/4 |
| K- 07 20 05 54 | 0 - 2.5 bar | 50,0 | G 1/4 |
| K- 07 20 05 55 | 0 - 4.0 bar | 50,0 | G 1/4 |
| K- 07 20 05 56 | 0 - 6.0 bar | 50,0 | G 1/4 |
| K- 07 20 05 57 | 0 - 10.0 bar | 50,0 | G 1/4 |
| K- 07 20 05 58 | 0 - 16.0 bar | 50,0 | G 1/4 |
| K- 07 20 05 59 | 0 - 25.0 bar | 50,0 | G 1/4 |
| K- 07 20 05 60 | 0 - 40.0 bar | 50,0 | G 1/4 |
| K- 07 20 05 61 | 0 - 100.0 bar | 50,0 | G 1/4 |
| K- 07 20 05 62 | 0 - 160.0 bar | 50,0 | G 1/4 |
| K- 07 20 05 63 | 0 - 60.0 bar | 50,0 | G 1/4 |