

K-TR PA 612

Plastic pipes made of polyamide PA 12 (10 pcs.)

HANSA FLEX

Características

| | |
|-------------------------|---|
| Temperatura de servicio | -60 °C to +100 °C (PA 12) |
| Características | Resistant to corrosion, vibration, impact, ageing, high pressures and heat |
| Longitud de tubo | 3 m |
| Unidad de embalaje | 10 lengths (O.D. 28 mm in packs of 5 lengths), only sold in complete packaging units! |
| Material | Polyamid PA 12, hard (according to DIN 73378) |



Nota

Operating pressure with 2.5 x overpressure safety!
Otras especificaciones a petición.

Descripción

Push-in fittings - aluminium pipes - plastic pipes - take-off points. The flexible, maintenance-free compressed air installation system from compressor to take-off point. For Ø 12 mm to Ø 32 mm pipe systems and for Ø 4 mm to Ø 12 mm pneumatic applications

Artículo

| Denominación | Ø exterior tubo (mm) | Ø interior tubo (mm) | Presión máx. de servicio a 20°C (bar) | Color |
|----------------|----------------------|----------------------|---------------------------------------|-------|
| K- 07 10 04 57 | 12 | 9 | 38 | azul |
| K- 07 10 04 59 | 12 | 9 | 38 | negro |
| K- 07 10 04 61 | 15 | 12 | 25 | azul |
| K- 07 10 04 63 | 15 | 12 | 25 | negro |
| K- 07 10 04 65 | 18 | 14 | 28 | azul |
| K- 07 10 04 67 | 18 | 14 | 28 | negro |
| K- 07 10 04 69 | 22 | 18 | 22 | azul |
| K- 07 10 04 71 | 22 | 18 | 22 | negro |
| K- 07 10 04 73 | 28 | 23 | 20 | azul |
| K- 07 10 04 75 | 28 | 23 | 20 | negro |