

K-TR PA 12

Plastic pipes made of polyamide PA 12 (20 pcs.)

HANSA FLEX

Características

Temperatura de servicio	-60 °C to +100 °C (PA 12)
Características	Resistant to corrosion, vibration, impact, ageing, high pressures and heat
Longitud de tubo	3 m
Unidad de embalaje	20 lengths (O.D. 28 mm in packs of 10 lengths), only sold in complete packaging units!
Material	Polyamid PA 12, hard (according to DIN 73378)



Nota

Operating pressure with 2.5 x overpressure safety!
Otras especificaciones a petición.

Descripción

Push-in fittings - aluminium pipes - plastic pipes - take-off points. The flexible, maintenance-free compressed air installation system from compressor to take-off point. For Ø 12 mm to Ø 32 mm pipe systems and for Ø 4 mm to Ø 12 mm pneumatic applications

Artículo

Denominación	Ø exterior tubo (mm)	Ø interior tubo (mm)	Presión máx. de servicio a 20°C (bar)	Color
K- 07 10 04 56	12	9	38	azul
K- 07 10 04 58	12	9	38	negro
K- 07 10 04 60	15	12	25	azul
K- 07 10 04 62	15	12	25	negro
K- 07 10 04 64	18	14	28	azul
K- 07 10 04 66	18	14	28	negro
K- 07 10 04 68	22	18	22	azul
K- 07 10 04 70	22	18	22	negro
K- 07 10 04 72	28	23	20	azul
K- 07 10 04 74	28	23	20	negro