

# K-TR PA 12

Plastic pipes made of polyamide PA 12 (20 pcs.)

**HANSA FLEX**

## Características

Temperatura de servicio	-60 °C to +100 °C (PA 12)
Características	Resistant to corrosion, vibration, impact, ageing, high pressures and heat
Longitud de tubo	3 m
Unidad de embalaje	20 lengths (O.D. 28 mm in packs of 10 lengths), only sold in complete packaging units!
Material	Polyamid PA 12, hard (according to DIN 73378)



## Nota

Operating pressure with 2.5 x overpressure safety!  
Otras especificaciones a petición.

## Descripción

Push-in fittings - aluminium pipes - plastic pipes - take-off points. The flexible, maintenance-free compressed air installation system from compressor to take-off point. For Ø 12 mm to Ø 32 mm pipe systems and for Ø 4 mm to Ø 12 mm pneumatic applications

## Artículo

Denominación	Ø exterior tubo (mm)	Ø interior tubo (mm)	Presión máx. de servicio a 20°C (bar)	Color
K- 07 10 04 56	12	9	38	azul
K- 07 10 04 58	12	9	38	negro
K- 07 10 04 60	15	12	25	azul
K- 07 10 04 62	15	12	25	negro
K- 07 10 04 64	18	14	28	azul
K- 07 10 04 66	18	14	28	negro
K- 07 10 04 68	22	18	22	azul
K- 07 10 04 70	22	18	22	negro
K- 07 10 04 72	28	23	20	azul
K- 07 10 04 74	28	23	20	negro