

K-SPIR SCHL

Spiral hose, without fittings

Características

Aplicación	Air, gases, oils, greases, fuels, organic and inorganic substances
Temperatura de servicio	-40 °C to +100 °C



Nota

Otras especificaciones a petición.

Descripción

These hoses allow gaseous and liquid media to flow safely and efficiently (Air, gases, oils, greases, fuels, organic and inorganic substances). Thanks to their small coil diameter, they are compact, easy to handle and lightweight. Very good recoil force owing to the use of nylon 12 (PA).

Artículo

Denominación	Ø Manguera int. (mm)	Ø Manguera ext. (mm)	Ø Espiral ext. (mm)	Torsiones	Max. working pressure resistance at 23° C (bar)	Longitud máx. de trabajo (m)
K- 07 10 07 51	3,1	4,7	38	144	22	10,0
K- 07 10 07 52	4,8	6,3	75	140	16	22,5
K- 07 10 07 53	6,3	7,9	75	135	13	22,5
K- 07 10 07 49	7,9	9,5	115	90	12	22,5
K- 07 10 07 50	9,5	11,8	140	70	11	22,5

Accesorios

K-DREHBARE VERSCHR KNICK	Swivel adapters with kink protector
K-STARRE VERSCHRAUBUNG	Rigid adapters with kink protector