

# K-SPIR SCHL DREH VERSCHRAU V

Spiral hose, with swivel adapter and kink protector, braided

**HANSA FLEX**

## Características

Tipo de conexión	with kink protector, swivel type
Temperatura de servicio	-40 °C to +74 °C



## Nota

Otras especificaciones a petición.

## Descripción

Standard type or with braided reinforcements for high pressures. These exceptionally elastic polyurethane hoses boast a recoil force similar to that of conventional nylon spiral hose, but with less tendency to loop and significantly better resistance to abrasion. There is consequently less danger of scratching coated or sensitive surfaces. The hose is extremely flexible and non-kinking.

## Artículo

Denominación	Rosca	Ø Manguera int. (mm)	Ø Manguera ext. (mm)	Ø espira exterior (mm)	Max. working pressure resistance at 23° C (bar)	Longitud máx. de trabajo (m)
K- 07 10 07 43	G 1/4	6,3	9,5	42	14	3,0
K- 07 10 07 44	G 1/4	6,3	9,5	42	14	6,0
K- 07 10 07 45	G 1/4	6,3	9,5	42	14	7,5
K- 07 10 07 46	G 3/8	8,0	12,0	55	14	3,0
K- 07 10 07 47	G 3/8	8,0	12,0	55	14	6,0
K- 07 10 07 48	G 3/8	8,0	12,0	55	14	7,5

## Accesorios

K-DREHBARE VERSCHRAUBUNG Swivel adapters