

K-VSEH 3-KRAFT

Receptacle combinations »3-Kraft«

HANSA FLEX

Características

Carcasa	Amaplast with hinged cover
Integrado en la carcasa	Hanging eyelets, wall mounting fixing and standing feet
Versión	Pre-wired
Entradas de línea	Top: 1 x M 32, 1 x M 25, 2 x M 20; Side: 1 x M 25; One opening at the top for pneumatic connection or grabrails (all introductions to break)
Tipo de protecc.	IP 44



Nota

Otras especificaciones a petición.

Descripción

Receptacle combination with low power, high power or combined connections. Equipped with a pneumatic connection (DN 7.2 coupling with 9 mm stem).

Artículo

Denominación	Equipamiento	Color
K- 07 10 03 50	3 Schuko socket 16 A 2p + E 230 V	amarillo
K- 07 10 03 49	2 Schuko socket 16 A 2p + E 230 V, 1 CEEform socket 16 A 5p 400 V	plata

Accesorios

K-VT 2 KUPPL 7,2 STECKNIP MS	Distributors with 2 quick disconnect couplings DN 7.2, brass with push in plug DN 7.2 - DN 7.8
K-ZUBEH VSEH 3 KRAFT AIRKRAFT	Accessories for receptacle combinations »3-Kraft« and »airkraft«