


# K-VERSCHLUSSNIPPEL IG POM

Self-sealing plugs, POM

**HANSA FLEX**

## Características

<b>Presión de servicio</b>	See table. All values referred to a medium temperature of 50 °C (static working pressure)
<b>Flujo de aire</b>	440 l/min (G 1/8), 840 l/min (G 1/4), 1.280 l/min (G 3/8), 1.950 l/min (G 1/2), 4.500 l/min (G 3/4) (at 6 bar and $\Delta p = 0,5$ bar)
<b>Temper. de medios</b>	-20 °C to +90 °C
<b>Carcasa, manguito</b>	POM (Delrin), white
<b>Válv.</b>	Stainless steel 1.4305
<b>Muelles, anillo de muelle, bolas</b>	stain less steel
<b>Material obturador</b>	NBR



## Nota

Otras especificaciones a petición.

## Descripción

Hydraulic couplings, both sides sealing, for liquid media acc. to ISO 7241, B Series.

## Artículo

Denominación	Conexión	Presión de servicio (bar)	Longitud (mm)	NW	SW (mm)
<b>K- 07 40 39 58</b>	G 1/8 female	15,0	29,5	4,3	14
<b>K- 07 40 39 59</b>	G 1/4 female	15,0	35,3	6,0	19
<b>K- 07 40 39 60</b>	G 3/8 female	15,0	39,0	7,5	22
<b>K- 07 40 39 61</b>	G 1/2 female	10,0	48,0	11,0	27
<b>K- 07 40 39 62</b>	G 3/4 female	10,0	60,0	13,0	36