


K-VERSCHLUSSNIPPEL IG POM

Self-sealing plugs, POM

HANSA FLEX

Características

| | |
|---|---|
| Presión de servicio | See table. All values referred to a medium temperature of 50 °C (static working pressure) |
| Flujo de aire | 440 l/min (G 1/8), 840 l/min (G 1/4), 1.280 l/min (G 3/8), 1.950 l/min (G 1/2), 4.500 l/min (G 3/4) (at 6 bar and $\Delta p = 0,5$ bar) |
| Temper. de medios | -20 °C to +90 °C |
| Carcasa, manguito | POM (Delrin), white |
| Válv. | Stainless steel 1.4305 |
| Muelles, anillo de muelle, bolas | stain less steel |
| Material obturador | NBR |



Nota

Otras especificaciones a petición.

Descripción

Hydraulic couplings, both sides sealing, for liquid media acc. to ISO 7241, B Series.

Artículo

| Denominación | Conexión | Presión de servicio (bar) | Longitud (mm) | NW | SW (mm) |
|-----------------------|--------------|---------------------------|---------------|------|---------|
| K- 07 40 39 58 | G 1/8 female | 15,0 | 29,5 | 4,3 | 14 |
| K- 07 40 39 59 | G 1/4 female | 15,0 | 35,3 | 6,0 | 19 |
| K- 07 40 39 60 | G 3/8 female | 15,0 | 39,0 | 7,5 | 22 |
| K- 07 40 39 61 | G 1/2 female | 10,0 | 48,0 | 11,0 | 27 |
| K- 07 40 39 62 | G 3/4 female | 10,0 | 60,0 | 13,0 | 36 |