


K-LKM 5 UWB

Non-interchangeable quick disconnect couplings DN 5

HANSA FLEX

Características

Presión de servicio	0 - 35 bar, maximum static working pressure (non-pulsating)
Flujo de aire	560 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Temper. de medios	-20 °C to +100 °C
Casquillo de desbloqueo	Anodised aluminium
Muelles, anillo de muelle, bolas	stain less steel
Material obturador	NBR



Nota

Standard push-in plugs for couplings DN 5 and DN 7.2 – DN 7.8 are compatible with these non-interchangeable couplings. Otras especificaciones a petición.

Descripción

One-hand quick disconnect couplings with a large bore. Different media can be connected safely and non-interchangeably even when space is restricted, thanks to the colour-coded coupling and plug and the different coupling profiles defined for each of the four colours. Only couplings and plugs of the same colour fit together.

Artículo

Denominación	Conexión	Color	Longitud (mm)	SW (mm)
K- 07 35 06 80	G 1/8 male	verde	45,0	14
K- 07 35 06 81	G 1/4 male	verde	47,0	17
K- 07 35 06 82	G 1/8 female	verde	45,0	14
K- 07 35 06 83	G 1/4 female	verde	47,0	17
K- 07 35 06 84	G 1/8 male	Brown	45,0	14
K- 07 35 06 85	G 1/4 male	Brown	47,0	17
K- 07 35 06 86	G 1/8 female	Brown	45,0	14
K- 07 35 06 87	G 1/4 female	Brown	47,0	17
K- 07 35 06 88	G 1/8 male	azul	45,0	14
K- 07 35 06 89	G 1/4 male	azul	47,0	17
K- 07 35 06 90	G 1/8 female	azul	45,0	14
K- 07 35 06 91	G 1/4 female	azul	47,0	17
K- 07 35 06 92	G 1/8 male	rojo	45,0	14
K- 07 35 06 93	G 1/4 male	rojo	47,0	17
K- 07 35 06 94	G 1/8 female	rojo	45,0	14
K- 07 35 06 95	G 1/4 female	rojo	47,0	17