


K-LKM 7,8 UWB

Non-interchangeable quick disconnect couplings DN 7.8

HANSA FLEX

Características

Presión de servicio	0 - 35 bar, maximum static working pressure (non-pulsating)
Flujo de aire	1.800 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Temper. de medios	-20 °C to +100 °C
Carcasa	Brass
Válv.	Die-cast zinc, nickel-plated
Casquillo de desbloqueo	Anodised aluminium
Muelles, anillo de muelle, bolas	stain less steel
Material obturador	NBR



Nota

Standard push-in plugs for couplings DN 5 and DN 7.2 – DN 7.8 are compatible with these non-interchangeable couplings. Otras especificaciones a petición.

Descripción

One-hand quick disconnect couplings with a large bore. Different media can be connected safely and non-interchangeably even when space is restricted, thanks to the colour-coded coupling and plug and the different coupling profiles defined for each of the four colours. Only couplings and plugs of the same colour fit together.

Artículo

Denominación	Conexión	Color	Longitud (mm)	SW (mm)
K- 07 35 08 01	G 1/4 male	verde	57,5	19
K- 07 35 08 02	G 3/8 male	verde	57,5	19
K- 07 35 08 03	G 1/4 female	verde	55,5	19
K- 07 35 08 04	G 3/8 female	verde	54,5	19
K- 07 35 08 05	G 1/4 male	Brown	57,5	19
K- 07 35 08 06	G 3/8 male	Brown	57,5	19
K- 07 35 08 07	G 1/4 female	Brown	55,5	19
K- 07 35 08 08	G 3/8 female	Brown	54,5	19
K- 07 35 08 09	G 1/4 male	azul	57,5	19
K- 07 35 08 10	G 3/8 male	azul	57,5	19
K- 07 35 08 11	G 1/4 female	azul	55,5	19
K- 07 35 08 12	G 3/8 female	azul	54,5	19
K- 07 35 08 13	G 1/4 male	rojo	57,5	19
K- 07 35 08 14	G 3/8 male	rojo	57,5	19
K- 07 35 08 15	G 1/4 female	rojo	55,5	19
K- 07 35 08 16	G 3/8 female	rojo	54,5	19