

K-INLINE-EJEKTTOREN VR

Inline ejectors »VR«, screw connection

HANSA FLEX

Características


Características Vacuum generator with high maximum vacuum level (85% vacuum)
No moving parts, which means no wear and no maintenance
ultra small footprint, suitable for confined spaces
minimal air consumption
\nlow noise

Aplicación by screwing / plugging into the distribution beam
direct attachment to the suction pad
for handling various workpieces

Carcasa Aluminium eloxed (type VR)

Sistema de boquilla Brass (type VR)

Conexión Conexión insertables



Nota

Otras especificaciones a petición.

Descripción

For vacuum generation directly at the point of use. For direct installation between the suction pad and the compressed air supply. Purely pneumatic vacuum generator that operates on the Venturi principle. Compressed air enters the ejector and flows through a nozzle. This results in a vacuum immediately behind the nozzle outlet, and air is drawn in through the vacuum inlet. This air and the driving air leave the ejector and enter the atmosphere via the exhaust air outlet.

Artículo

Denominación	Tamaño de boquilla	Conex. aire de escape	Conexión de aire comprimido	Conex. vacío	Grado de evacuación	Consumo de aire aspir. (L/min)	Capacidad máx. aspiración (L/min)	Longitud (mm)	Presión de servicio (bar)
K- 07 45 01 29	0,7	M 5 male	G 1/4 IG	G1/8 female	90 %	21,0	14,0	35,0	5,0
K- 07 45 01 30	0,9	M 5 male	G 1/4 IG	G1/8 female	89 %	36,0	21,0	35,0	5,0