


K-INLINE-EJEKTTOREN SLP

Inline ejectors »SLP«, plug connection

HANSA FLEX

Características

Características	Vacuum generator with high maximum vacuum level (85% vacuum) No moving parts, which means no wear and no maintenance ultra small footprint, suitable for confined spaces minimal air consumption low noise
Aplicación	by screwing / plugging into the distribution beam direct attachment to the suction pad for handling various workpieces
Carcasa	plastic (Typ SLP)
Sistema de boquilla	Brass (type VR)
Conexión	thread connector



Nota

Otras especificaciones a petición.

Descripción

For vacuum generation directly at the point of use. For direct installation between the suction pad and the compressed air supply. Purely pneumatic vacuum generator that operates on the Venturi principle. Compressed air enters the ejector and flows through a nozzle. This results in a vacuum immediately behind the nozzle outlet, and air is drawn in through the vacuum inlet. This air and the driving air leave the ejector and enter the atmosphere via the exhaust air outlet.

Artículo

Denominación	Tamaño de boquilla	Conex. aire de escape	Conexión de aire comprimido	Conex. vacío	Grado de evacuación	Consumo de aire aspir. (L/min)	Capacidad máx. aspiración (L/min)	Longitud (mm)	Presión de servicio (bar)
K- 07 45 01 27	0,5	-	4 mm	4 mm	85 %	13,0	8,0	57,0	4,5
K- 07 45 01 28	0,7	-	4 mm	4 mm	85 %	25,0	16,0	57,0	4,5