

K-BALGSAUGER 1,5 NBR

Bellows suction pads, round, 1.5 folds, material NBR

HANSA FLEX

Características

Características high rigidity of the upper fold
Soft, tapered sealing lips
Support surfaces on the bottom
high suction power
optimum damping effect
very good adaptation to curved or uneven material

Campo de aplicación Handling of highly uneven parts (e.g.tubes)
Handling of highly sensitive parts



Nota

Mini-sensor with housing and connection cable, analogue or digital output signal. Minimum size and low weight combined with high measuring accuracy. Otras especificaciones a petición.

Descripción

Robust and hard-wearing suction pad with a single sealing lip. Used wherever objects (parts, packing materials, etc.) need to be lifted, transported, turned over or handled in some other manner. It is also ideal when it is necessary to compensate varying workpiece heights or uneven surfaces or to handle easily damaged parts. It acts as the connecting element between the vacuum generator and the workpiece.

Información adicional

Attention: The price does not include connection nipples. Please order separately.

Artículo

| Denominación | Boquilla de conex. rosca exterior | Boquilla de conex. rosca interior | Altura cons. con boquilla rosca exterior | Altura cons. con boquilla rosca interior | Ø (mm) |
|----------------|-----------------------------------|-----------------------------------|--|--|--------|
| K- 07 45 00 29 | K-07450002 / K-07450004 | K-07450007 | 21 / 22 | 28 | 11,0 |
| K- 07 45 00 31 | K-07450002 / K-07450004 | K-07450007 | 21 / 22 | 28 | 14,0 |
| K- 07 45 00 33 | K-07450002 / K-07450004 | K-07450007 | 24 / 25 | 31 | 16,0 |
| K- 07 45 00 35 | K-07450002 / K-07450004 | K-07450007 | 20,5 / 21,5 | 27,5 | 20,0 |
| K- 07 45 00 37 | K-07450004 | K-07450007 | 29 | 35 | 25,0 |
| K- 07 45 00 39 | K-07450003 | K-07450006 | 31 | 42 | 33,0 |
| K- 07 45 00 41 | K-07450003 | K-07450006 | 32 | 43 | 43,0 |
| K- 07 45 00 43 | K-07450003 | K-07450006 | 38 | 49 | 53,0 |

Accesorios

K-ANSCHLUSSNIP BALGSAUGER Connection nipples for bellows suction pads, round, 1.5 and 2.5 folds