

K-FLACHSAUGER RUND NBR

Flat suction pads, round, material NBR

HANSA FLEX

Características

| | |
|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Características | minimal priming high lateral forces realized good stability in the sucked state Support surfaces on the bottom fastest cycle times high suction force with small dimensions |
|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

| | |
|----------------------------|---------------------------------------------------------------------------------------------------|
| Campo de aplicación | Handling of parts with plain to an slightly rough surface like sheets, \ncartons, glass, plastics |
|----------------------------|---------------------------------------------------------------------------------------------------|



Nota

Mini-sensor with housing and connection cable, analogue or digital output signal. Minimum size and low weight combined with high measuring accuracy. Otras especificaciones a petición.

Descripción

Robust and hard-wearing suction pad with a single sealing lip. Used wherever objects (parts, packing materials, etc.) need to be lifted, transported, turned over or handled in some other manner. It is also ideal when it is necessary to handle smooth or slightly rough surfaces. Due to its flat shape, it can grip the workpiece in a very short time and withstand the forces that result from fast movement of the object during handling. It acts as the connecting element between the vacuum generator and the workpiece.

Información adicional

Attention: The price does not include connection nipples. Please order separately.

Artículo

| Denominación | Boquilla de conex. rosca exterior | Boquilla de conex. rosca interior | Altura cons. con boquilla rosca exterior | Altura cons. con boquilla rosca interior | Ø (mm) |
|----------------|-----------------------------------|-----------------------------------|------------------------------------------|------------------------------------------|-----------|
| K- 07 45 00 87 | K-07450014 | - | 6 | - | 3,5 |
| K- 07 45 00 89 | K-07450015 | K-07450022 | 11,5 | 16,5 | 5,0 |
| K- 07 45 00 91 | K-07450015 | K-07450022 | 12 | 17 | 8,0 |
| K- 07 45 00 93 | K-07450015 / K-07450017 | K-07450022 / K-07450024 | 12,5 | 17,5 / 23,5 | 10,0 |
| K- 07 45 00 95 | K-07450018 | K-07450025 | 13 | 24 | 15,0 |
| K- 07 45 00 97 | K-07450019 | K-07450026 | 15 | 26 | 20,0 |
| K- 07 45 00 99 | K-07450020 | K-07450027 | 19 | 30 | 25,0 |
| K- 07 45 01 01 | K-07450020 | K-07450027 | 17 | 28 | 30,0 |
| K- 07 45 01 03 | K-07450020 | K-07450027 | 19 | 30 | 35,0 |
| K- 07 45 01 05 | K-07450020 | K-07450027 | 19 | 30 | 40,0 |
| K- 07 45 01 07 | K-07450021 | K-07450028 | 20 | 31 | 50,0 |
| K- 07 45 01 09 | K-07450016 | K-07450016 | 23 | 39 | 60,0 |
| K- 07 45 01 11 | K-07450016 | K-07450016 | 25 | 41 | 80,0 |

Accesorios

| | |
|-----------------------------|------------------------------------------|
| K-ANSCHLUSSNIP FLACHSAUG AG | Connection nipples for flat suction pads |
| K-ANSCHLUSSNIP FLACHSAUG IG | Connection nipples for flat suction pads |