

K-SAUGPLATTENAUFHAENGUNG

Flexible suction pad mountings

HANSA FLEX

Características

Aplicación For handling of workpieces with sloping using large-area vacuum gripper
Handling of large plates that can sag when lifting
In combination with spring plungers to compensate height-differences and Unevenness

Características especiales very good adaptation to oblique workpiece surfaces
automatic Rückstellung in die Ausgangslage
vacuum-tight design with integrated protection against damage



Nota

Otras especificaciones a petición.

Descripción

Flexible suction pad mounting. By flexing in all directions, this mounting allows the suction pad to better adapt itself to sloping workpieces.

Artículo

| Denominación | Rosca 1 interior | Rosca 2 exterior | H (mm) | Material | L1 (mm) | L2 (mm) | Ángulo W (°) | Carga vertical (N/m ²) | Momento de flexión (N/m ²) | SW (mm) |
|----------------|------------------|------------------|-----------|---------------|------------|------------|-----------------|---------------------------------------|---|------------|
| K- 07 45 01 47 | G 1/4 | M 10 x 1.25 | 27,0 | Steel, rubber | 10,5 | 8,0 | 12 | 500 | 8,0 | 17 |
| K- 07 45 01 48 | G 1/4 | G 1/4 | 27,0 | Steel, rubber | 12,0 | 12,0 | 12 | 750 | 10,0 | 17 |