

# K-DRS MDR 5 M ENTLASTU VENT

»MDR 5« pressure switches, with unloading valve / on/off switch / flange 1/4, without motor protection circuit

**HANSA FLEX**

## Características

Temper. de medios	-5 °C to +80 °C
Pres. de desconexión máx.	16 bar
Capacidad de conmut.	5,5 kW
Tipo de contacto	NC (3-pole)
Frecuencia máx. de maniobras	120 (electrical), 600 (mechanical)
Tipo de protecc.	IP 54



## Nota

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211)  
Otras especificaciones a petición.

## Descripción

Three-phase version

## Indicaciones para pedidos

For use on devices that have to be vented whenever they are turned off, either because of safety regulations or for technical reasons. The pneumatic devices are disconnected from the system and simultaneously vented each time they are shut off.

## Información adicional

Important: A thermal, 3-pole overcurrent relay must be ordered together with these switches. Without this relay, the on/off mechanism does not work.

## Artículo

Denominación	Conexión de aire comprimido	Rango de ajuste
K- 07 30 24 25	G 1/2	2,0 - 11,0 bar
K- 07 30 24 27	G 1/2	2,5 - 16,0 bar