

K-BKR LEICHT IG AG

Ball valves, lightweight type, female/male thread

HANSA FLEX

Características

Campo de aplicación	Compressed air, water, non-toxic and non-corrosive gases, heating systems, agriculture
Presión de servicio	Max. 40 bar
Temperatura de servicio	-15 °C to +90 °C
Descripción de rosca	G thread acc. DIN EN ISO 228-1
Carcasa	Nickel-plated brass
Palanca	Alu, painted black
Bola	Chrome-plated brass
Obturación esférica	PTFE
Obturación de husillo	HNBR / EPDM / PTFE. 2 O-Rings (HNBR / EPDM) 1 gasket (PTFE) additional PTFE-gasket



Nota

Otras especificaciones a petición.

Artículo

Denominación	DN	Rosca	A (mm)	B (mm)	L (mm)
K- 07 30 00 25	8	G 1/4	85,0	42,0	44,0
K- 07 30 00 26	10	G 3/8	85,0	42,0	51,0
K- 07 30 00 27	15	G 1/2	85,0	46,0	60,0
K- 07 30 00 28	20	G 3/4	105,0	53,0	70,0
K- 07 30 00 29	25	G 1	105,0	57,0	79,0
K- 07 30 00 30	32	G 1 1/4	130,0	70,0	91,0
K- 07 30 00 31	40	G 1 1/2	130,0	76,0	104,0
K- 07 30 00 32	50	G 2	165,0	92,0	122,0