K-BKR STAN EIN FED VA


Stainless steel ball valves, single-acting actuator - spring to close

HANSA FLEX

Características

Construcción	Pneumatic actuators, in double- or single acting version, with integrated end-position feedback
Presión de servicio	max. 63 bar (depending on temperature and nominal size)
Temperatura de servicio	-20 °C to +70°C
Áng. giro	90 °
Interfaces normalizadas	Interface actuator / valve: four or eight threaded holes in the drive housing according to EN ISO 5211, Interface actuator / S
Presión de control	5.5 bar
Adaptador válv.	Acc. to NAMUR
Accion.	aluminium eloxed
Obt. de accionam.	NBR
Ll. bola	Stainless steel 1.4401,with ISO-flange plate
Obtur. grifo esférico	PTFE





Nota

Otras especificaciones a petición.

Descripción

2-way cock, 3-piece, full bore

Artículo

Denominación	DN	Rosca	A (mm)	B (mm)	D (mm)	L (mm)	SW (mm)
K- 07 30 02 59	15	Rp 1/2	133,0	144,0	24,0	75,0	29
K- 07 30 02 60	15	Rp 1/2	116,0	135,0	24,0	75,0	29
K- 07 30 02 61	20	Rp 3/4	133,0	148,0	27,0	80,0	35
K- 07 30 02 62	25	Rp 1	137,0	170,0	33,0	90,0	41
K- 07 30 02 63	32	Rp 1 1/4	161,0	188,0	37,0	110,0	50
K- 07 30 02 64	40	Rp 1 1/2	180,0	198,0	40,0	120,0	58
K- 07 30 02 65	50	Rp 2	209,0	224,0	50,0	140,0	74
K- 07 30 02 66	65	Rp 2 1/2	221,0	268,0	60,0	185,0	85
K- 07 30 02 67	80	Rp 3	221,0	280,0	67,0	205,0	100

Hemos revisado cuidadosamente esta publicación, pero no obstante no podemos excluir los errores y no garantizamos los datos que constan aquí.