


# K-NADELVENTILE VA

Needle valves

**HANSA FLEX**

## Características

Presión de servicio	max. 400 bar (at 20 °C); max. 250 bar (at G 1 - 20 °C)
Temperatura de servicio	-20 °C to +120 °C
Material obturador	PTFE
Carcasa	Stainless steel 1.4571
Rueda manual	Plastic
Material	sealing: PTFE



## Nota

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211)  
Otras especificaciones a petición.

## Indicaciones para pedidos

For use on devices that have to be vented whenever they are turned off, either because of safety regulations or for technical reasons. The pneumatic devices are disconnected from the system and simultaneously vented each time they are shut off.

## Información adicional

Port sizes G 1 1/4, G 1 1/2 and G 2 available on request

## Artículo

Denominación	DN	Rosca	A (mm)	C (mm)	L (mm)
K- 07 30 24 03	4	G 1/8	50,0	74,0	50,0
K- 07 30 24 04	5	G 1/4	50,0	73,0	50,0
K- 07 30 24 05	6	G 3/8	50,0	72,0	55,0
K- 07 30 24 06	8	G 1/2	63,0	83,0	60,0
K- 07 30 24 07	10	G 3/4	63,0	100,0	75,0
K- 07 30 24 08	12	G 1	80,0	110,0	100,0