


K-T AG DREH

Male branch tees, swivel type, parallel male thread

HANSA FLEX

Características

Presión de servicio	Max. 16 bar (at +20 °C)
Temperatura de servicio	-20 °C to +70 °C
Material	Latón niquelado
Anillo de presión	Hostaform (black nickel-plated for Ø 10, 12)
Junta tórica	NBR, siliconefree
Pinza de sujeción	Stainless steel AISI 316



Nota

Otras especificaciones a petición.

Descripción

Economy yet very high-quality series of push-in fittings made of nickel-plated brass. Compact, space-saving, lightweight design. An O-ring in the fillet at the end of the thread guarantees a tight connection for all male thread parts, even on rough surfaces.

Artículo

Denominación	Rosca	para Ø exterior de tubo flexible	L1 (mm)	L2 (mm)	SW
K- 07 40 29 85	G 1/8	4 mm	35,0	18,5	13 mm
K- 07 40 29 86	G 1/8	6 mm	42,0	18,5	13 mm
K- 07 40 29 87	G 1/8	8 mm	46,0	20,5	13 mm
K- 07 40 29 83	G 1/4	6 mm	42,0	22,5	13 mm
K- 07 40 29 84	G 1/4	8 mm	46,0	22,5	13 mm
K- 07 40 29 82	G 1/4	10 mm	51,0	24,5	16 mm