

K-W90 VERBINDER POM

Union elbows

HANSA FLEX

Características

| | |
|---------------------------|---|
| Presión de funcionamiento | 0 - 16 bar (4 - 8 mm); 0 - 10 bar (10 - 28 mm) |
| Temperatura de servicio | -20 °C to +70 °C in air; +1 °C to +70 °C in water |
| Material | Acetalpolymerisat (POM) |
| Material obturador | NBR |



Nota

Otras especificaciones a petición.

Descripción

Lightweight, push-in fittings distinguished by high strength, toughness, resistance to abrasion and impact resistance - ideal for a wide range of applications. Plastic and metal tubes are connected together quickly and easily. Suitable for compressed air or liquids, with good resistance to a large number of chemicals.

Artículo

| Denominación | para Ø exterior de tubo flexible | L1 (mm) | L2 (mm) |
|----------------|----------------------------------|------------|------------|
| K- 07 40 28 52 | 4 mm | 25,1 | 25,1 |
| K- 07 40 28 53 | 5 mm | 25,1 | 25,1 |
| K- 07 40 28 54 | 6 mm | 28,1 | 28,1 |
| K- 07 40 28 55 | 8 mm | 30,9 | 30,9 |
| K- 07 40 28 56 | 10 mm | 36,2 | 36,2 |
| K- 07 40 28 57 | 12 mm | 45,0 | 45,0 |
| K- 07 40 28 58 | 15 mm | 51,4 | 51,4 |
| K- 07 40 28 59 | 18 mm | 60,9 | 60,9 |
| K- 07 40 28 60 | 22 mm | 67,4 | 67,4 |
| K- 07 40 28 61 | 28 mm | 87,7 | 87,7 |