# K-KONDENSA DRUKODRAIM PLUS

Drain for compressed air condensate

## Características

| | |
|---|---|
| **Potencia de conex. filtro** | 100 m3/min |
| **Potencia conex. compresor** | 10 m3/min |
| **Potencia conex. secador** | 20 m3/min |



## Nota

Otras especificaciones a petición.

## Descripción

Compact and exceptionally reliable, level-controlled drain for compressed air condensate. The condensate enters the integrated collecting tank, in which the level is continuously monitored. When the condensate reaches the maximum mark, the pilot valve opens and the condensate is forced into the discharge line by the system pressure. The valve closes again when the level reaches the minimum mark. Benefits of »drukodrain plus«: No pressure loss, Diaphragm protected by integrated cup filter, Test button for manual outlet, Auto-reset function, Suitable for all condensate types.

## Indicaciones para pedidos

The following voltages on request: 24 VDC, 24 VAC DC, 24 VAC / 50 Hz, 110 VAC / 50 Hz, 115 V / 50 Hz

## Artículo

| Denominación | Presión de servicio en bar | Tensión |
|---|---|---|
| **K- 07 25 09 24** | 0.2 - 16 bar | 230 VAC / 50 Hz |

*Hemos revisado cuidadosamente esta publicación, pero no obstante no podemos excluir los errores y no garantizamos los datos que constan aquí.*