

# K-DBV MANO 1/4"

Pressure limiting valves size 1/4

## Características

<b>Construcción</b>	Spring-loaded, non-return diaphragm valve with adjustable opening pressure
<b>Temper. de medios</b>	max. 60 °C
<b>Temp. entorno</b>	Max. 60 °C
<b>Material obturador</b>	NBR
<b>Caperuza elást.</b>	POM/brass
<b>Carcasa</b>	Die-cast zinc, painted silver
<b>Membrana</b>	NBR



## Nota

Otras especificaciones a petición.

## Descripción

Manually adjustable overflow valves. For protecting pneumatic systems against damage caused by excess pressure.

## Artículo

Denominación	Rosca	Rango de regulación	A (mm)	B	C (mm)	D (mm)
K- 07 25 01 93	G 1/4	0.1 - 2.0 bar	43,0	70,0 mm	10,0	60,0
K- 07 25 01 94	G 1/4	0.1 - 3.0 bar	43,0	70,0 mm	10,0	60,0
K- 07 25 01 95	G 1/4	0.15 - 7.0 bar	43,0	70,0 mm	10,0	60,0
K- 07 25 01 96	G 1/4	0.5 - 10.0 bar	43,0	70,0 mm	10,0	60,0

## Piezas de repuesto

K-HALTERBAUSATZ	Holder
K-SCHALTTAFELMUTTER	Nut
K-VERSCHLEI-SATZ	Set of wearing parts
K-SCHALLDAE SINTERBR AG 569	Silencers, sintered bronze, flat type with male thread, 569 Series
K-GERAETESTECKER	Coupling socket