

K-VORFI PC-BEHÄLTER MULTIFIX MINI

Pre-filters with polycarbonate bowl

HANSA FLEX

Características

| | |
|-----------------------|--|
| Presión de entrada | Max. 16 bar |
| Temper. de medios | max. 60 °C |
| Temp. entorno | Max. 60 °C |
| Finura del filtro | 0,30 µm |
| Efectividad | 99.999 % |
| Material obturador | NBR |
| Cartucho de filtro | Paper-POM |
| Carcasa | Die-cast zinc |
| Drain valve | Semi-automatic |
| Medic. valor de flujo | FV at P1 = 6 bar and pressure drop $\Delta p = 0.02$ bar |



Nota

If several devices in the »multifix-mini« Series are assembled together, the maximum working pressure is 12 bar.
Otras especificaciones a petición.

Descripción

Micro-filters for compliance with strict compressed air purity requirements. Suitable for all applications where standard filters do not afford the desired efficiency.

Artículo

| Denominación | Rosca | Flujo de paso (L/min) | A (mm) | B | C (mm) | D (mm) | DN |
|----------------|-------|-----------------------|--------|----------|--------|--------|----|
| K- 07 25 10 64 | G 1/8 | 130 | 40,0 | 114,8 mm | 12,3 | 102,5 | 5 |
| K- 07 25 10 66 | G 1/4 | 160 | 40,0 | 138,1 mm | 12,3 | 125,8 | 5 |

Piezas de repuesto

| | |
|------------------------|-----------------------|
| K-AUTOMAT ABLASSVENTIL | Automatic drain valve |
| K-KOPPELPAKET MEHR | Coupling packet |