

# K-DRG DRVS MULTIFIX

Pressure regulators with pressure supply at both ends

**HANSA FLEX**

## Características

|                       |  |
|-----------------------|--|
| Presión de entrada    | Max. 16 bar  |
| Temper. de medios     | max. 60 °C   |
| Temp. entorno         | Max. 60 °C   |
| Material obturador    | NBR  |
| Caperuza elást.       | POM-brass  |
| Carcasa               | Die-cast zinc  |
| Medic. valor de flujo | At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar |



## Nota

Otras especificaciones a petición.

## Descripción

Diaphragm pressure regulators with self-relieving design for mounting side by side. The pressure setting can be locked by pushing the knob down. <br>By assembling two or more controllers together, it is possible to supply several working air circuits with different output pressures via a single supply line.

## Indicaciones para pedidos

The port for the output pressure (P2) is on the rear! K-07250031: G 1/4, K-07250034: G 1/2. Lockable pressure regulators K-07250030 available on request.

## Artículo

| Denominación   | Rosca | Rango de regulación | Flujo de paso (L/min) | A (mm) | B        | C (mm) | D (mm) | DN | Tamaño constructivo |
|----------------|-------|---------------------|-----------------------|--------|----------|--------|--------|----|---------------------|
| K- 07 25 00 31 | G 1/4 | 0.1 - 3 bar         | 2000                  | 47,8   | 94,8 mm  | 67,0   | 27,8   | 6  | 1                   |
| K- 07 25 00 32 | G 1/4 | 0.2 - 6 bar         | 2000                  | 47,8   | 94,8 mm  | 67,0   | 27,8   | 6  | 1                   |
| K- 07 25 00 30 | G 1/4 | 0.5 - 10 bar        | 2000                  | 47,8   | 94,8 mm  | 67,0   | 27,8   | 6  | 1                   |
| K- 07 25 00 34 | G 1/2 | 0.1 - 3 bar         | 5500                  | 68,8   | 134,1 mm | 99,0   | 35,1   | 15 | 2                   |
| K- 07 25 00 35 | G 1/2 | 0.2 - 6 bar         | 5500                  | 68,8   | 134,1 mm | 99,0   | 35,1   | 15 | 2                   |
| K- 07 25 00 33 | G 1/2 | 0.5 - 10 bar        | 5500                  | 68,8   | 134,1 mm | 99,0   | 35,1   | 15 | 2                   |

## Piezas de repuesto

|                          |                      |
|--------------------------|----------------------|
| K-HALTERBAUSATZ          | Holder               |
| K-SCHALTAFELMÜTTER       | Nut                  |
| K-HALTERBAUSATZ MULTIFIX | Holder               |
| K-KOPPELPAKET MEHR       | Coupling packet      |
| K-KOPPELPAKET SCHMA      | Coupling packet      |
| K-VERSCHLEI-SATZ         | Set of wearing parts |