

K-FI PC-BEHÄLTER SCHUTZK MULTIFIX

Filters with polycarbonate bowl and bowl guard

HANSA FLEX

Características

Presión de entrada	Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl)
Temper. de medios	max. 60 °C
Temp. entorno	Max. 60 °C
Ancho de poros en elemento filtrante	5 µm (BG 1 / BG 2), 40 µm (BG 3)
Carcasa	Die-cast zinc, Aluminium for G 1 variant
Drain valve	Semi-automatic
Medic. valor de flujo	At P1 = 6 bar and pressure drop $\Delta p = 1$ bar



Nota

Otras especificaciones a petición.

Descripción

Centrifugal separators with a sintered filter element.

Artículo

Denominación	Rosca	Flujo de paso (L/min)	A (mm)	B	C (mm)	D (mm)	DN	Tamaño constructivo
K- 07 25 00 48	G 1/4	2100	47,8	152,1 mm	27,0	125,1	6	1
K- 07 25 00 51	G 3/8	2100	47,8	152,1 mm	27,0	125,1	10	1
K- 07 25 00 54	G 1/2	4000	68,8	181,8 mm	34,5	147,3	15	2
K- 07 25 00 57	G 3/4	4000	68,8	181,8 mm	34,5	147,3	20	2
K- 07 25 00 60	G 1	8000	100,0	305,8 mm	52,0	253,8	25	3

Piezas de repuesto

K-HALTERBAUSATZ MULTIFIX	Holder
K-KOPPELPAKET MEHR	Coupling packet
K-KOPPELPAKET SCHMA	Coupling packet
K-METALLBEHÄLTER OELER MULTIFIX	Metal tank oiler
K-PC-BEHÄLTER FILTER MULTIFIX	Polycarbonate tank filter
K-SCHUTZKORB G	Protective cage
K-FILTERELEMENT	Filter element
K-AUTOMAT ABLASSVENTIL	Automatic drain valve