

K-NEBELOELER PC-BEHÄLTER S MULTIFIX

Oil-mist lubricators with polycarbonate bowl and bowl guard

HANSA FLEX

Características

Presión de entrada	Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl)
Temper. de medios	max. 60 °C
Temp. entorno	Max. 60 °C
Material obturador	NBR
Carcasa	Die-cast zinc, Aluminium for G 1 variant
Suplem. de goteo	PA (polycarbonate bowl), Zinc-glass-NBR (metal bowl)
Drain valve	Manual
Tipo de aceite	CL 32 acc. to DIN 51517 - ISO VG 32
Medic. valor de flujo	At P1 = 6 bar and pressure drop $\Delta p = 1$ bar



Nota

Otras especificaciones a petición.

Descripción

Proportional lubricators, oil can be filled under pressure.

Artículo

Denominación	Rosca	Flujo de paso (L/min)	A (mm)	B	C (mm)	D (mm)	DN	Tamaño constructivo
K- 07 25 00 93	G 1/4	1900	47,8	167,8 mm	58,0	109,8	6	1
K- 07 25 00 96	G 3/8	1900	47,8	167,8 mm	58,0	109,8	10	1
K- 07 25 00 99	G 1/2	5000	68,8	198,6 mm	66,1	132,5	15	2
K- 07 25 01 02	G 3/4	5000	68,8	198,6 mm	66,1	132,5	20	2
K- 07 25 01 05	G 1	18000	100,0	324,3 mm	82,7	241,6	25	3

Piezas de repuesto

K-HALTERBAUSATZ MULTIFIX	Holder
K-KOPPELPAKET MEHR	Coupling packet
K-KOPPELPAKET SCHMA	Coupling packet
K-METALLBEHÄLTER OELER MULTIFIX	Metal tank oiler
K-PC-BEHÄLTER FILTER MULTIFIX	Polycarbonate tank filter
K-SCHUTZKORB G	Protective cage
K-TROPFAUFSATZ POLYCARBO 1	Drip attachment polycarbonate
K-TROPFAUFSATZ METALL	Drip attachment metal