# K-WTEH 2-TLG MET SICH TROPF MULTIFI


Service units, 2-piece with metal bowl and sight glass, metal sight dome

HANSA-FLEX

## Características

| | |
|---|---|
| **Presión de entrada** | Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl) |
| **Temper. de medios** | max. 60 °C |
| **Temp. entorno** | Max. 60 °C |
| **Ancho de poros en elemento filtrante** | 5 µm (BG 1 / BG 2), 40 µm (BG 3) |
| **Material obturador** | NBR |
| **Caperuza elást.** | POM-brass |
| **Carcasa** | Die-cast zinc, Aluminium for G 1 variant |
| **Suplem. de goteo** | PA (polycarbonate bowl), Zinc-glass-NBR (metal bowl) |
| **Drain valve** | Semi-automatic |
| **Medic. valor de flujo** | At P1 = 8 bar, P2 = 6 bar and pressure drop Δp = 1 bar |






## Nota

Otras especificaciones a petición.

## Descripción

Two-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

## Indicaciones para pedidos

2-piece service units are also available in other control ranges (0.1 - 3 bar, 0.2 - 6 bar and 0.5 - 16 bar) and in lockable version. Please ask for more information.

## Información adicional

1500 l/min: P1: 10 bar, P2: 7 bar, Δp ≤ 0.1 bar.

## Artículo

| Denominación | Rosca | Rango de regulación | Flujo de paso (L/min) | A (mm) | B | C (mm) | D (mm) | DN | Tamaño constructivo |
|---|---|---|---|---|---|---|---|---|---|
| **K- 07 25 01 30** | G 1/4 | 0.5 - 10 bar | 1100 | 93,0 | 196,0 mm | 67,0 | 129,0 | 6 | 1 |
| **K- 07 25 01 33** | G 3/8 | 0.5 - 10 bar | 1100 | 93,0 | 196,0 mm | 67,0 | 129,0 | 10 | 1 |
| **K- 07 25 01 36** | G 1/2 | 0.5 - 10 bar | 3500 | 136,0 | 248,0 mm | 97,0 | 151,0 | 15 | 2 |
| **K- 07 25 01 39** | G 3/4 | 0.5 - 10 bar | 3500 | 136,0 | 248,0 mm | 97,0 | 151,0 | 20 | 2 |
| **K- 07 25 01 42** | G 1 | 0.5 - 10 bar | 10500 | 200,0 | 385,0 mm | 128,0 | 257,0 | 25 | 3 |

## Piezas de repuesto

| | |
|---|---|
| **K-HALTERBAUSATZ MULTIFIX** | Holder |
| **K-KOPPELPAKET MEHR** | Coupling packet |
| **K-METALLBEHAELTER OELER MULTIFIX** | Metal tank oiler |
| **K-PC-BEHAELTER FILTER MULTIFIX** | Polycarbonate tank filter |
| **K-SCHUTZKORB G** | Protective cage |
| **K-TROPFAUFSATZ POLYCARBO 1** | Drip attachment polycarbonate |
| **K-TROPFAUFSATZ METALL** | Drip attachment metal |
| **K-FILTERELEMENT** | Filter element |
| **K-AUTOMAT ABLASSVENTIL** | Automatic drain valve |
| **K-VERSCHLEI-SATZ** | Set of wearing parts |
| **K-HALTERBAUSATZ** | Holder |
| **K-SCHALTTAFELMUTTER** | Nut |
| **K-KOPPELPAKET SCHMA** | Coupling packet |

*Hemos revisado cuidadosamente esta publicación, pero no obstante no podemos excluir los errores y no garantizamos los datos que constan aquí.*