


K-WTEH 3-TLG PC-BEHÄEL SCHUTZK MULT

Service units, 3-piece with polycarbonate bowl and bowl guard

HANSA FLEX

Características

Presión de entrada	Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl)
Temper. de medios	max. 60 °C
Temp. entorno	Max. 60 °C
Ancho de poros en elemento filtrante	5 µm (BG 1 / BG 2), 40 µm (BG 3)
Material obturador	NBR
Caperuza elást.	POM-brass
Carcasa	Die-cast zinc, Aluminium for G 1 variant
Suplem. de goteo	PA (polycarbonate bowl), Zinc-glass-NBR (metal bowl)
Drain valve	Semi-automatic
Medic. valor de flujo	At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar



Nota

Otras especificaciones a petición.

Descripción

Three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, centrifugal separator and proportional lubricator.

Indicaciones para pedidos

3-piece service units are also available in other control ranges (0.1 - 3 bar, 0.2 - 6 bar and 0.5 - 16 bar) and in lockable version. Please ask for more information.

Información adicional

1500 l/min: P1: 10 bar, P2: 7 bar, $\Delta p \leq 0.1$ bar.

Artículo

Denominación	Rosca	Rango de regulación	Flujo de paso (L/min)	A (mm)	B	C (mm)	D (mm)	DN	Tamaño constructivo
K- 07 25 01 12	G 1/4	0.5 - 10 bar	1100	137,8	192,1 mm	67,0	125,1	6	1
K- 07 25 01 15	G 3/8	0.5 - 10 bar	1100	137,8	192,1 mm	67,0	125,1	10	1
K- 07 25 01 18	G 1/2	0.5 - 10 bar	3000	200,8	246,3 mm	99,0	147,3	15	2
K- 07 25 01 21	G 3/4	0.5 - 10 bar	3000	200,8	246,3 mm	99,0	147,3	25	2
K- 07 25 01 24	G 1	0.5 - 10 bar	11300	300,0	381,4 mm	128,0	253,8	25	3

Piezas de repuesto

K-HALTERBAUSATZ	Holder
K-SCHALTAFELMUTTER	Nut
K-HALTERBAUSATZ MULTIFIX	Holder
K-KOPPELPAKET MEHR	Coupling packet
K-KOPPELPAKET SCHMA	Coupling packet
K-METALLBEHÄELTER OELER MULTIFIX	Metal tank oiler
K-PC-BEHÄELTER FILTER MULTIFIX	Polycarbonate tank filter
K-SCHUTZKORB G	Protective cage
K-TROPFAUFSATZ POLYCARBO 1	Drip attachment polycarbonate
K-TROPFAUFSATZ METALL	Drip attachment metal
K-FILTERELEMENT	Filter element
K-AUTOMAT ABLASSVENTIL	Automatic drain valve
K-VERSCHLEI-SATZ	Set of wearing parts